

# Three Phase Hybrid Inverter

SUN-8/10/12K-SG05LP3-EU-SM2

The Deye logo features the word "Deye" in a blue sans-serif font, with a red vertical bar to the left of the letter 'D'.

## Deye



- 100** 100% unbalanced output, each phase; Max. output up to 50% rated power
- AC** AC couple to retrofit existing solar system
- 10** Max. 10 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- 240** Max. charging/discharging current of 240A
- 48** 48V low voltage battery, transformer isolation design
- 6** 6 time periods for battery charging/discharging
- Generator** Support storing energy from diesel generator



# Technical Data

Battery Input Data			
Battery Type	Lead-acid or Lithium-ion		
Battery Voltage Range (V)	40-60		
Max. Charging Current (A)	190	210	240
Max. Discharging Current (A)	190	210	240
Charging Strategy for Li-ion Battery	Self-adaption to BMS		
Number of Battery Input	1		
PV String Input Data			
Max. PV Input Power (W)	12000	15000	18000
Max. PV Input Voltage (V)	800		
Start-up Voltage (V)	160		
MPPT Voltage Range (V)	200-650		
Rated PV Input Voltage (V)	550		
Max. Operating PV Input Current (A)	20+20		
Max. Input Short-Circuit Current (A)	30+30		
No. of MPP Trackers/ No. of Strings per MPP Tracker	2/1+1		
AC Input/Output Data			
Rated AC Input/Output Active Power (W)	8000	10000	12000
Max. AC Input/Output Apparent Power (VA)	8800	11000	13200
Rated AC Input/Output Current (A)	12.2/11.6	15.2/14.5	18.2/17.4
Max. AC Input/Output Current (A)	13.4/12.8	16.7/16	20/19.2
Max. Three-phase Unbalanced Output Current (A)	18.2/17.4	22.8/21.8	27.3/26.1
Max. Continuous AC Passthrough (grid to load) (A)	45		
Peak Power (off-grid) (W)	2 times of rated power, 10s		
Power Factor Adjustment Range	0.8 leading to 0.8 lagging		
Rated Input/Output Voltage/Range (V)	220/380V, 230/400V 0.85Un-1.1Un		
Rated Input/Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65		
Grid Connection Form	3L+N+PE		
Total Current Harmonic Distortion THDi	<3% (of nominal power)		
DC Injection Current	<0.5% In		
Efficiency			
Max. Efficiency	97.6%		
Euro Efficiency	97.0%		
MPPT Efficiency	>99%		
Equipment Protection			
Integrated	DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection AC Output Overvoltage Protection, AC Output Short Circuit Protection, Thermal Protection DC Terminal Insulation Impedance Monitoring, DC Component Monitoring, Ground Fault Current Monitoring Power Network Monitoring, Island Protection Monitoring, Earth Fault Detection, DC Input Switch Overvoltage Load Drop Protection, Residual Current (RCD) Detection, Surge protection level		
Surge Protection Level	TYPE II(DC), TYPE II(AC)		
Interface			
Communication Interface	RS485/RS232/CAN		
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)		
General Data			
Operating Temperature Range (°C)	-40 to +60 , >45 Derating		
Permissible Ambient Humidity	0-100%		
Permissible Altitude	3000m		
Noise (dB)	≤55		
Ingress Protection(IP) Rating	IP 65		
Inverter Topology	Non-Isolated		
Over Voltage Category	OVC II(DC), OVC III(AC)		
Cabinet Size (WxHxD mm)	386×660×253 (Excluding Connectors and Brackets)		
Weight (kg)	35.2		
Type of Cooling	Intelligent Air Cooling		
Warranty	5 Years/10 Years the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to Warranty Policy		
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105		
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2		



Calma Sp. z o.o.  
ul. Składowa 13, 26-800 Białobrzegi  
NIP: 7981483124

+48 536 514 888  
biuro@calma.pl  
www.b2b.calma.pl

Zgłoś się na szkolenie!  
**536 514 588**

